

*Compact and Powerful Pick/Carry Lift* 



inches wide


## LOAD CHART

JER**CRANE** 

0

BOOM SECTION 1 + 2 EXTENDED												
Working Radius (ft.)	2.0	2.5	3.0	3.5	4.0	4.5						
Outriggers Not Engaged (lbs)	1520	1490	1443	1431	1392	1369						
Outriggers Maximum (lbs.)	1520	1490	1443	1431	1392	1369						
BOOM SECTION 1 + 2 + 3 EXTENDED												
Working Radius (ft.)	3.0	3.5	4.0	4.5	5.0	5.5	6.0	6.5	7.0	7.5	8.0	8.5
Outriggers Maximum (lbs.)	1367	1294	1242	1227	1221	1054	1037	1023	1005	987	975	940
BOOM SECTION 1 + 2 + 3 + 4 EXTENDED												
Working Radius (ft.)	8.0	8.5	9.0	9.5	10.0	10.5	11.0	11.5	12.0	12.5	13	
Outriggers Maximum (lbs.)	450	440	424	421	405	402	400	397	388	380	373	
Capacity subject to chapte												

Capacity subject to change



**22ft** Tip Height 1,990<sup>lbs</sup> Capacity **48V** Battery Power

Engine / Motor	<b>Electric ZCO</b>								
Battery	48V 200Ah Battery, with battery meter on dashboard								
Crane Capacity	1,520 lbs								
Drive Radius (ft.)	180° by Steering								
Dimensions When Folded (ft.)	31 inches x 63 inches x 72 inches (W x H x L)								
Weight	3,100 lbs								
Boom	Boom Type:	Telescoping Boom, with box construction							
	Boom Length: 5.6 ft (retracted) to 18 ft (extended)								
Traction System	Hydrostatic Drive Motor								
	Wheels:         1 Rear Cushion   2 Front - 18x7-R8 Superelastic								
Winch	Capacity: 1520 lbs at 4th layer (Single-Line)								
	Winch Speed:         249 ft/min   Wire Rope Length: 275 ft								
Safety Features	• Tilt Alarm		Hook Safety Latch						
	Anti Two-Block		Automatic Stop for leaving Minimum Wire Rope						
	Hydraulic Capac	city Alert	Automatic Stop and Alarm for Overwinding						
	Counterbalance	Valves for Boom Cylinders	Emergency Stop Button						
Optional Accessories:	Searcher Hook								
	<ul> <li>SPYDERWEB 5-Axis fixed Glass Manipulator - Attaches directly to boom for rigid application</li> </ul>								
	Wood's Powr-Grip Vacuum Lifter								
	Low-Temperature Kit								
	Non-Marking Tires     Specifications subject to chan								

22

0



5326 W. Mohave St | Phoenix, AZ 85043 844.264.8994 | 602.442.4000 Visit us on the web at **SmileyLiftingSolutions.com** 

## **Preliminary Data**

Product specifications are subject to change without notice. No specific training or license is required to operate the PC094 SPYDERCRANE in most areas, but operators are responsible for knowing and meeting all safety requirements and regulations.