

Compact and Powerful Pick/Carry Lift

ft overall length

31 inches wide


LOAD CHART

BOOM SECTION 1 EXTENDED						
		.66	0	-1	Working Radius (ft.)	
		1900	1900	1900	Stabilizers Open (lbs)	
		1000	1025	1025	Stabilizers Stowed (lbs)	
BOOM SECTION 1 + 2 EXTENDED						
	4.83	4.75	4.3	1.6	Working Radius (ft.)	
	1200	1250	1350	1450	Stabilizers Open (lbs)	
	425	500	500	650	Stabilizers Stowed (lbs)	
BOOM SECTION 1 + 2 + 3 EXTENDED						
8.5	7.8	6.6	5.3	4.1	Working Radius (ft.)	
750	800	950	1000	1050	Stabilizers Open (lbs)	
350	350	350	400	400	Stabilizers Stowed (lbs)	
BOOM SECTION 1 + 2 + 3 + 4 EXTENDED						
		13	10.4	7.3	Working Radius (ft.)	
		450	500	500	Stabilizers Open (lbs)	
		N/A	N/A	N/A	Stabilizers Stowed (lbs)	
		450	10.4 500	7.3 500	Working Radius (ft.) Stabilizers Open (lbs)	

Capacity subject to change

WORKING RANGE

1,900^{lbs} Capacity





SPECIFICATIONS

Engine / Motor			etific ZCIO			
Battery	48V 200Ah Battery, with battery meter on dashboard					
Crane Capacity	1,900 lbs					
Drive Radius (ft.)	360° by Steering					
Dimensions When Folded (ft.)	31 inches x 63 inches x 72 inches (W x H x L)					
Weight	3,100 lbs					
Boom	Boom Type: 4-Section Hydraulically Telescoping Boom, with box construction					
	Boom Length: 5.6 ft (retracted) to 18 ft (extended)					
Traction System	Hydrostatic Drive Motor					
	Wheels: 2 Rear Cushion 2 Front - 18x7-R8 Superelastic					
Winch	Capacity: 1900 lbs at 4th layer (Single-Line)					
	Winch Speed: 249 ft/min Wire Rope Length: 155 ft					
Safety Features	Anti Two-Block Counterbalance Emergency Stop	Valves for Boom Cylinders	Hook Safety Latch Automatic Stop for leaving Minimum Wire Rope			
Optional Accessories:	Searcher Hook SPYDERWEB 5-Axis fixed Glass Manipulator - Attaches directly to boom for rigid application Wood's Powr-Grip Vacuum Lifter Low-Temperature Kit Non-Marking Tires Specifications subject to change					



5326 W. Mohave St | Phoenix, AZ 85043 844.264.8994 | 602.442.4000

Visit us on the web at **SmileyLiftingSolutions.com**