



Compact and Powerful Pick/Carry Lift


inches wide

LOAD CHART

BOOM SECTION 1 + 2 EXTENDED				
4.83				
1200				
425				
BOOM SECTION 1 + 2 + 3 EXTENDED				
7.8	8.5			
800	750			
350	350			
BOOM SECTION 1 + 2 + 3 + 4 EXTENDED				

WORKING RANGE

Olbs Capacity



SPECIFICATIONS

Engine / Motor		Ballery Powered Sign	etific ZCIO		
Battery	48V 200Ah Battery, with battery meter on dashboard				
Crane Capacity	1,900 lbs				
Drive Radius (ft.)	360° by Steering				
Dimensions When Folded (ft.)	31 inches x 68 inches x 94 inches (W x H x L)				
Weight	2,900 lbs				
Boom	Boom Type: 4-Section Hydraulically Telescoping Boom, with box construction Boom Length: 5.8ft (retracted) to 18 ft (extended)				
Traction System	Hydrostatic Drive Motor				
	Wheels:	neels: 2 Rear Cushion 2 Front - 18x7-R8 Superelastic			
Winch	Capacity:	1900 lbs at 4th layer (Single-Line)			
	Winch Speed: 103 ft/min Wire Rope Length: 155 ft				
Safety Features	Anti Two-Block Counterbalance Valves for Boom Cylinders Emergency Stop Button		Hook Safety Latch Automatic Stop for leaving Minimum Wire Rope		
Optional Accessories:	Searcher Hook SPYDERWEB 5-Axis fixed Glass Manipulator - Attaches directly to boom for rigid application Wood's Powr-Grip Vacuum Lifter Low-Temperature Kit Non-Marking Tires Specifications subject to change				



5326 W. Mohave St | Phoenix, AZ 85043

844.264.8994 | 602.442.4000

Visit us on the web at SmileyLiftingSolutions.com